Features

- Slim-line enclosures
- Up to 5 metres scanning range
- No range setting required
- Diagnostic and status indicators
- Two part system
- Dual electronic outputs
- 24V DC operation
- M12 connectors
- Very fast response time
- 1 year warranty
- IP65 protection rating

Specification

Number of Beams	8 - 64
Object Detection	30mm
Detection Zone	200mm to 1600mm
Range	0.5 – 5m
Light Type	Infra-Red 880nm
Response Time	15ms standard (1ms option available)
Operating Temperature	0°C to +50°C
Light Curtain Enclosure	IP65 (HxWxD) Hx30x25mm
Status Indicators	Tx - Red = Beam 'ok'
	Tx - Yellow = 'Power'
	Rx - Red = 'Blocked'
	RX - Green = 'Clear'
	RX - Yellow = 'Power'
Power Supply	22 - 28 V DC
	Ripple <10% (diode protected)
Current Consumption	60mA per 8 beams
Light Curtain Connection	M12 4 core
Finish	Silver anodised aluminium extrusion
Classification	CE mark
Warranty	1 Year
OUTPUTS	
Outputs	2 x Electronic NPN 100mA



Pywell Road · Corby · Northants · NN17 5XJ


Tel: +44 (0) 1536 401313 Fax: +44 (0) 1536 268954

Email: sales@smartscan.com

www.smartscan.com


Product Range

30mm Object De	tection Capability	Range 0.5 to 5m		
Model Number	Number of beams	Detection zone	Overall length mm	
090-208	8	200	246	
090-416	16	400	446	
090-624	24	600	646	
090-832	32	800	846	
090-1040	40	1000	1046	
090-1248	48	1200	1246	
090-1456	56	1400	1446	
090-1664	64	1600	1646	



Accessories

Model Number	Description
090-001	Mounting bracket kit
090-002	3m cable with straight plug
090-005	3m cable with angle plug
090-003	10m cable with straight plug
090-004	10m cable with angle plug



Product Conformity

The 9000 Series is CE marked and together with our ISO 9001:2000 certification full confidence can be placed in the quality, reliability and above all the safety of Smartscan light curtains and equipment.

DISTRIBUTOR



SMARTSCAN Machinery Guarding Systems

Security Systems

AND MANY OTHERS

9000 Series Light Curtains

